



# NUTRUNNERS

HP 0,6 KW 0,44

Series 72/50



## Performances and dimensions

Model	Free speed r/min	Speed at max power r/min	Torque at max power Nm	Starting torque Nm	Torque Nm	Quote "L" mm	Weight Kg.	Air consum l/sec.
M72/50L4	600	300	14	20	25	176	1,6	8,5
P72/50L4	600	300	14	20	25	184	1,6	8,5
M72/50LT	435	220	19	25	33	176	1,6	8,5
P72/50LT	435	220	19	25	33	184	1,6	8,5
M72/50N4	235	120	30	35	45	194	1,7	8,5
P72/50N4	235	120	30	35	45	202	1,7	8,5
M72/50NT	170	85	43	50	65	194	1,7	8,5
P72/50NT	170	85	43	50	65	202	1,7	8,5
M72/50P4	130	65	57	60	80	194	1,7	8,5
P72/50P4	130	65	57	60	80	202	1,7	8,5
M72/50PT	95	47	79	90	115	194	1,7	8,5
P72/50PT	95	47	79	90	115	202	1,7	8,5

**ATTENTION**  
All data are based on a  
working pressure of 7 bar

**Lubrication:** 2-3 drops/1' continuous operation  
4-6 drops/1' intermittent operation

**Filtration:** Use 64 µ filtration or better

**Axial load:** Not admitted

**Operative temperature:** da-20° a +80°

